




This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			C45-1-1	1	MANUAL KNOB RELEASE	6061		2
			C45-3-2	1	LATCH ROLLER PIN	O-1		3
		B/O	C45-3-2-1	2	SNAP RING	STEEL	Ø3/8 (KAMAN 1400-0037)	3
			C45-3-3	1	LATCH ROLLER	4140/4142		3
			C45-3-4	2	LINK PIN	O-1		3
		B/O	C45-3-4-1	4	RETAINING RING	BERYLLIUM COPPER	3/16 SHAFT (MCMaster-CARR #98410A110)	3
		B/O	C45-3-5	2	SPACER	TEFLON	(MCMaster-CARR #95606A180)	3
			C45-3-6	1	LATCH	17-4 S.S.		3
			C45-3-7	1	LINK	O-1		3
			C45-3-8A	1	ACTUATOR SHAFT BUSHING	AL BRONZE 630	(MCMaster-CARR #8203K612) MODIFIED	3
			C45-3-8B	1	ACTUATOR SHAFT BUSHING SOLENOID SIDE	AL BRONZE 630	(MCMaster-CARR #8203K612) MODIFIED	3
		B/O	C45-3-9	1	LEVER SPRING	303 S.S.	Ø .045 X 9-1/4 DENDOFF	3
			C45-3-11	1	ACTUATOR	17-4 S.S.		3
		B/O	C45-3-12	1	DU BEARING		(KAMAN 06DU06)	3
			C45-4-1	2	TRUNNION BUSHING	AL-BRONZE 630	(MCMaster-CARR #8203K812) MODIFIED	2
			C45-4-4KA	1	C45 LOAD BEAM KEEPERLESS ASSY.			2
			C45-4-5	1	LOAD BEAM SPACER	4140/4142 Q&T		2
		B/O	C45-5-1	1	LEVER STOP PIN	STEEL	1/4 X 1-3/8 (MCMaster-CARR #98381A545)	2
			C45-5-2	1	LEVER STOP	304 S.S.		2
			C45-7-1	1	LOAD BEAM BUMPER	POLYURETHANE		2
			C45-7-2	2	LOCK BUMPER	PLOYURETHANE		2
			C45-8-1-2	2	SOLENOID NUT	304 S.S.		2
			C45-8-2	1	SOLENOID ASSY		(REF: H-2553-020)	2
			C45-8-4	1	SOLENOID COVER GASKET	BLENDED RUBBER		2
			C45-8-5	1	SOLENOID COVER	6061		2
			C45-9-1	1	CLOCK SPRING COVER	6061		2
		B/O	C45-9-2	1	CLOCK SPRING	303 S.S.	.03 X .75 X 15 DENDOFF SPRING	2
		B/O	C45-10-1	1	SPRING PIN	S.S.	1/4 X 1.0 (MCMaster-CARR #92373A183)	2
		B/O	C45-11-2	2	LOCATING PIN	S.S.	Ø3/16 X 1 (MCMaster-CARR #90145A510)	2
			C45-12-1	2	LOCK BUSHING	4140/4142		3
			C45-12-2	1	LOCK SHAFT	4140/4142		3
			C45-12-4	1	LOCK ROLLER	4140/4142		3
			C45-12-5	1	LOCK ROLLER PIN	4140/4142		3
		B/O	C45-12-6	2	RETAINING RING	STEEL	(KAMAN #N1400-0050)	3
			C45-13-1	2	KEEPER BUSHING	4140/4142		3
			C45-13-3	1	KEEPER SHAFT	4140/4142		3
			C45-15	1	KEEPERLESS ADAPTER	4140/4142		3
			C60-2-1	1	SIDE PLATE	7075-T6		2
		B/O	C60-3-1	2	RADIAL BEARING		(KAMAN #1614 2RS)	3
			C60-3-10	1	LATCH SHAFT	17-4 S.S.		3
			C60-10-2	1	LOCK SPRING	302 S.S.	Ø.25 OD X Ø.026 WIRE (MCMaster-CARR #9665K85) MODIFIED	3
			C60-11-1	1	SIDE PLATE SOLENOID	7075-T6		3
			C60-12-3	1	LOCK	4140/4142		3
		B/O	C10-41	1	STRAIN RELIEF CONNECTOR	BRASS	1/2 TRADE SIZE (MCMaster-CARR #6907K14)	2
		B/O	C2-14-2	2	LABEL RIVETS 	18-8 S.S.	NO 4 (MCMaster-CARR #91654A106)	N/S
			600.1309	1	LABEL 	ALUMINUM		N/S
			600.1309-A	1	LABEL 	ALUMINUM		N/S
		B/O	AN4-23A	2	BOLT	STEEL	1/4-28 X 2.41	2
		B/O	AN5-21A	4	BOLT	STEEL	5/16-24 X 2.22	2
		B/O	AN960-416	3	WASHER	STEEL	1/4	2
		B/O	AN960-516	8	WASHER	STEEL	Ø5/16	2
		B/O	MS21044N5	4	LOCK NUT	S.S.	5/16	2
		B/O	MS27039-4-08	1	BOLT	STEEL	1/4-28 X .531	2
		B/O	188-FPSS-1/4 20-3/8	2	SET SCREW	S.S.	1/4-20 (MCMaster-CARR #92313A535)	2
		B/O	188-FSCS-1032-5/8	4	SCREW	S.S.	10-32 X 5/8 FSHCS (MCMaster-CARR #92210A303)	2
		B/O	EL-PLUG-M	1	MALE PLUG	PE High Density	(MCMaster-CARR #7216K5)	2
		B/O	EL 314-SJTOW 3/14	1	3 WIRE		(TEXCAN 314-SJTOW 3/14)	2
		B/O	32448	2	16-14 AWG KNIFE CONNECTOR		(ALLIED ELECTRONICS 32448)	2
		B/O		1	HEAT SHRINK TUBE	RUBBER	(MCMaster-CARR #2595K22)	N/S



REVISIONS							
REV	ECR	DESCRIPTION			DATE	INITIAL	APPROVED
1		RELEASED FOR PRODUCTION.			7/6/2015	DPD	JAG
2	15-0227	C45-5-1 CH'D B/O WAS Ø1/4 X 1-1/2 #98381A546 IS 1/4 X 1-3/8 #98381A545. CH'D P/NS: WAS C45-1-2 IS 188-FPSS-1/4 20-3/8. WAS C45-9-1-1 IS 188-FSCS-1032-5/8. MS27039-4-10 REPLACED WITH MS27039-4-08. CORD GRIP REPLACED WITH C10-41. 32446 REPLACED WITH 32448.			8/24/2015	DPD	JAG




NOTES:

 FOR REBUILD ONLY.

 FOR CUSTOMER REBUILD ONLY.

			
TITLE C60-K-HOOK			
DWG NO. C60-K			REV 2
MAT'L UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING		DRAWN BY: APPROVED  TREAT FINISH SPEC USED ON MODEL	
SCALE 1:4	DATE		SHEET 1 OF 3

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED



DART
AEROSPACE

TITLE	C60-K-HOOK
-------	------------

DWG NO.	
---------	--

C60-K

REV
2

	MAT'L
--	-------

DRAWN BY:

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

.XXX ± .005	FRACTIONS ± 1/8
.XX ± .01	ANGLES ± 5°

0	APPROV
---	--------

DIMENSIONS ARE IN INCHES

.XXX	± .005	FRACTIONS ± 1/8
.XX	± .01	ANGLES ± 5°
✓	± .1	

HEAT
TREAT

1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
2. DIMENSIONAL LIMITS APPLY AFTER PLATING

5.	SPEC
----	------

	USED ON MODEL
--	---------------





SCALE 1:4

DATE

SHEET 2 OF 3

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



NOTE:
4 LASER ENGRAVE DART LOGO, P/N, S/N, "MADE IN USA," WITHIN BOUNDARY.

TITLE		C60-K-HOOK	
DWG NO.		C60-K	
REV		2	
MATERIAL		DRAWN BY: D. Well	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		APPROVED	
.XXX ± .005		TREAT	
.XX ± .01		FINISH	
.X ± .1		SPEC	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R		USED ON MODEL	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING			
SCALE		DATE	
1:4		SHEET 3 OF 3	